- 1 -

MAGNETIC DISK DEVICE AND SERVO WRITE METHOD

BACKGROUND OF THE INVENTION

The present invention generally relates to magnetic disk devices such as hard disk drives, and particularly to a technique of writing servo signals for positioning magnetic heads on magnetic disks.

As one of servo write methods, there is known the self servo-write method for recording servo track information in a magnetic disk device by controlling the magnetic head (hereafter, simply referred to as head) and actuator of a product itself without using any external writing device. This method is concretely disclosed in Japanese Patent No. 2921604 (W096/28814) and JP-A-8-255448.

In the former, reference information for positioning a head, i.e., a servo signal, is written after a head is pressed against a stopper, and the amount of head-feeding, or pitch for positioning is calculated while being adjusted according to the amplitude of its reproduced waveform.

In the latter, the magnetic head is moved by using an external writing device within a clean room so that servo information as a reference can be previously recorded on a part of a magnetic disk (hereafter, simply referred to as disk), and the amount of head-feeding, or pitch for positioning is calculated by

reading the recorded pattern.

In the former, however, the regions over which information is written on the disk cannot be fixed, or determined because the head's core width varies, i.e., because very small read and write elements have their tolerances of mounting or size.

Moreover, in order to execute the latter, it is necessary to record a servo signal on part of the disk by using an external writing device. Thus, the latter has the drawback that it spoils the advantage of the self servo-write that does not need any external writing device. In addition, it requires a clean room as a large-scale facility.

SUMMARY OF THE INVENTION

The present invention is to provide the self servo-write capable of removing the necessity of using an external writing device for recording a preliminary servo signal, and definitely determining an information writing region by use of the magnetic disk device itself on the disk that this device has, thereby assuring a designed number of tracks to be recorded in this fixed region.

The above objective of the invention can be achieved by providing a magnetic disk device in which a servo-write method is executed by writing a recording region detecting signal on a magnetic disk that the magnetic disk device has when a magnetic head the

device itself has is initially loaded onto the disk at a stage where a positioning signal for the head is not recorded yet, and determining a servo signal writing region of the magnetic disk on the basis of the

5   position where the recording region detecting signal has been written on the disk.

According to the invention, the amount the head is fed when the servo signal is written can be adjusted on the basis of the amount the head is fed

10   according to a propagation-purpose pattern recorded in the radius direction of the disk between the ends of the servo signal writing region with one end selected as the position at which the recording region detecting signal has been written and with the other end selected

15   as a stop position at which the head is stopped by, for example, a stopper.

In addition, the magnetic disk device of the invention has a magnetic disk for storing information, a magnetic record head for recording information on the

20   disk, and a magnetic reproduce head for reproducing information from the disk, wherein the recording region detecting signal is written on the disk just when the head is loaded onto the disk on which any positioning signal for the head is not stored yet, and a region of

25   tracks to be recorded on the disk is determined on the basis of the position at which the recording region detecting signal has been written.

Moreover, according to the invention, just

when the head is initially moved, or fed onto the disk

from, for example, a ramp road on the outer periphery

side, a current is caused to flow to the head, thereby

writing a signal on the disk along the outermost

5 periphery. Then, the head is further fed toward the

inner periphery side, and fed back toward the outer

periphery side. When it is fed back toward the outer

periphery, the propagation-purpose signal is written at

a certain pitch. At this time, the signal written when

10 the head is initially loaded onto the disk will be

detected. This detected signal is recognized as the

outermost periphery of the region over which

information is to be written on the disk. Thus, a

track pitch necessary when a product-purpose servo

15 signal is written can be calculated from the distance

between the innermost periphery and the outermost

periphery, and from a designed number of tracks.

Therefore, since the servo-write can be performed by

use of the head that the magnetic disk device itself

20 has, it is not necessary to record servo tracks within

a clean room by using an external writing device as in

the prior art.

Additionally, according to the invention,

since the track region is provided between the position

25 at which the recording region detecting signal is

written, and the stop position at which the head is

stopped by a stopper, servo tracks can be recorded by

the magnetic head that each magnetic disk device has.

In addition, the recording region detecting signal is written in the loading area between the ramp road and the servo signal. Also, since the write current is caused to flow to the head only during the

5 time interval from when the magnetic head lies at a constant position on the ramp road to just when the magnetic head is loaded onto the disk, the recording region detecting signal can be written at a predetermined position on the magnetic disk.

10 Additionally, the time duration, or transition time in which the magnetic head is initially loaded onto the disk from a constant position at which the disk lies on the ramp road can be calculated from the distance the magnetic head has been moved and the speed at which the

15 head is moved, by means for making such calculation. According to the invention, the servo region can be easily determined by using the head the magnetic disk device itself has.

Moreover, when the head is fed back from the

20 stop position to which the head is regulated in its movement by the stopper to sequentially record the propagation-purpose pattern in the radius direction of the disk, and detects the recording region detected signal, the detected position is recognized as one end

25 of the track region, thus making it possible to easily find the servo signal recorded region.

Additionally, the pitch at which the head is fed to record a product-purpose servo signal can be

calculated from the number of times that the head is fed, to record the propagation-purpose pattern, back from the stop position to which the head is regulated by the stopper until the recording region detecting

5 signal is detected, and from a designed number of tracks, thus making it possible to assure the designed number of tracks.

According to the invention, when the magnetic disk device makes self servo-write operation, the

10 information written region on the magnetic disk can be determined by the head the device itself has, so that the designed number of tracks can be assured. Therefore, it is not necessary to provide an external writing device and a writing environment such as a

15 clean room.

Other objects, features and advantages of the invention will become apparent from the following description of the embodiments of the invention taken in conjunction with the accompanying drawings.

20 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of one embodiment of the magnetic disk device according to the invention.

FIG. 2 is a flowchart for a procedure of servo write according to the invention.

25 FIGS. 3A-3C are diagrams showing the movement of a head while it is writing a pattern signal in the invention.

FIG. 4 is a flowchart for a procedure of measuring the track width of head and R/W offset.

FIG. 5 is a graph showing the relation between VCM current and head position.

5   FIG. 6 is a diagram showing the movement of head at the time of measuring track width and R/W offset.

FIG. 7 is diagram showing propagation-purpose pattern signals and reproduced waveforms of written

10   signal at the loading time.

FIG. 8 is a flowchart for a procedure of calculating the feeding pitch for servo signal for product.

FIG. 9 is a pattern diagram of propagation

15   servo signal and pattern signal.

DESCRIPTION OF THE EMBODIMENTS

An embodiment of the invention will be first described briefly. According to this embodiment, in a magnetic disk device 100 as shown in FIG. 1, a head 102

20   as a product itself is used to record a servo signal (hereafter, called servo-write) on a disk 101 in which any information is not recorded yet.

In order to make servo-write, first the disk 101 and head 102 are properly built and sealed within a

25   housing, and then a current to head 102 is instantaneously turned on and off when the head 102 is loaded, so that a signal 110 for positioning can be

recorded on the outermost periphery of the disk. The

distance between the position of this recorded

positioning signal 110 and the innermost periphery 111

of the disk to which the head is regulated by a stopper

5 106 is a recordable region's width 112 for product use.

Then, servo-write is performed while the amount of head

feeding is being adjusted on the basis of the track

spacing calculated from the designed number of tracks.

FIG. 1 schematically shows the construction

10 of the magnetic disk device according to the invention,

and the flow of signal in the servo-write operation.

This embodiment will be further described in detail

with reference to FIG. 1. The magnetic disk device 100

has the disk 101 for storing information, and the head

15 102 for recording/reproducing a signal on/from the

disk. The head 102 is supported to be rotatable around

a pivot 104, and moved in any radial direction on disk

101 by an actuator 105.

In addition, a ramp road 103 is a retraction

20 place onto which the head 102 is retreated from the

disk surface. When servo-write is performed on this

magnetic disk device 100, an operation control circuit

unit 107 is mounted on the disk device so that it can

control the head 102 and actuator 105.

25 As described previously, the magnetic disk

device 100 of this embodiment does not use an external

writing device, but use the head 102 and actuator 105

provided within itself to record signals on disk 101,

and to again record new patterns with the head offset
on the basis of the reproduced signal of this recorded
pattern, thus forming a servo signal on the disk
recording region.

5   This operation control circuit unit 107 is
not necessarily the same as one for making the magnetic
disk device 100 operate as a product. The operation
control circuit unit 107 includes a write current
driver 107a for writing patterns, a pattern generator
10   107b, a preamplifier 107c for processing the reproduced
signal, a demodulator 107d, a VCM (voice coil motor)
driver 107e for driving the actuator, a controller 107f
for controlling these functions, and a memory 107g for
storing parameters that are required for the operation.

15   FIG. 2 shows a procedure (steps S) for servo-
write operation of the magnetic disk device having
those elements according to the invention. First, the
spindle is started to rotate, and reached to a
predetermined rotational speed (S 21).

20   Then, the actuator 105 is driven by the VCM
driver 107e to move the head 102 from the ramp road 103
onto the area on the disk 101 (hereafter, referred to
as loading of head) (S22).

       At the time of loading, the write current to
25   the head 102 is turned on so that a signal can be
written on the disk 101 at the same time. A constant
time after the writing of signal, the write current is
turned off so that the written signal can be recorded

only on the vicinity of the outermost periphery of the
disk 101 (S23).

At this time, although the head 102 lies on
the disk 101, other head positioning signals are not
5 recorded yet on the disk and thus the radial position
of head 102 on the disk 101 cannot be detected.
Therefore, after the loading, the head 102 is not
stopped but moved to the inner periphery of the disk
until the actuator 105 hits the stopper 106 on the
10 innermost periphery of the disk (S24).

Thereafter, a current 109 flowing in the VCM
is made constant on this innermost periphery so that
the actuator can be pressed against the stopper, or
that the head 102 can be substantially fixed in its
15 position. Then, the current 109 is changed to finely
adjust the position of head 102, and R/W offsets and
track width are measured (S25).

Further, the feed pitch is set on the basis
of the information of measured track width (S26), and a
20 servo pattern (hereafter, referred to as propagation-
purpose pattern) is recorded that is used to determine
the head position when a servo signal is recorded later
in the radial direction (S27).

When the propagation-purpose pattern is
25 recorded up to around the outermost periphery, the head
102 detects the initial pattern signal written at the
time of loading, and at this time it ends the recording
of propagating pattern from the innermost periphery

(S28).

Here, by using the relation between the amounts of head feeding from the inner periphery to the outer periphery, and the number of tracks of servo

5   pattern to be written, the device calculates the pitch of head feeding for writing a servo pattern (hereafter, called product-purpose servo signal) by which the head 102 can be located at a certain track in order to write/read information (S29).

10   Then, the product-purpose servo signal is again sequentially recorded toward the inner periphery, and the servo-write operation is finished when the product-purpose servo signal of a certain number of tracks has finally been completely written (S30).

15   The feature of the magnetic disk device of the invention, as described above, is to write a signal when the head is loaded at step 22 under the condition that any positioning signal is not yet recorded on the disk, and to make the outermost periphery on which the

20   signal 110 has been written be used as one end of the radial region 112 across which tracks are to be recorded in the radial direction.

Therefore, since the servo-write operation is performed to fix one end of the radial region across

25   which tracks are to be recorded on the disk in the radius direction, and store the number of steps that the head has been fed over the distance from the innermost periphery to the outermost periphery in order

to record the propagation-purpose pattern, there is an
advantage that, even though the head core width has a
distribution, or dispersion, the number of tracks
designed can be assured by recalculating the head
5   feeding pitch that is necessary for writing the
product-purpose servo signal on the basis of the ratio
of the head feeding pitch to the number of tracks
designed.

The procedure shown in FIG. 2 will be further
10 described in detail. A description will be made of the
procedure for the operation of writing a signal at the
time of loading. First, as at step 21, when the
spindle is started, the revolution speed is fixed to a
predetermined value. By causing a DC current to flow
15 to the actuator 105, the head 102 is urged to move
toward the outer periphery side and pressed against the
end of ramp road 103.

Then, when a DC current is again caused to
flow to the actuator 105 and to move it toward the
20 inner periphery, thereby making the loading of head 102
on the disk, a write current is simultaneously supplied
to the record head at time t_1 (301) at which the head
102 lies on the ramp road 103 as shown in FIG. 3A

In this embodiment, time t_1 (301) is when the
25 DC current is started to flow, i.e., when a counter-
electromotive force from the actuator 105 is detected,
and thereafter the write current to the record head is
turned off when the head 110 has initially reached onto

the disk 101 (time t_2 (302)).

The write end time t_2 (302) is determined as follows. The actuator 105 is controlled by a speed control method in which the counter-electromotive force from the actuator 105 itself is detected, as shown by the velocity curve in FIG. 3B.

Therefore, the write current to the record head is turned off at time t_2 (302) corresponding to a range (303) previously decided according to the size of ramp road 103 and the outermost periphery of disk 101. Thus, the signal 110 (shown in FIG. 3C) is written along the outermost periphery of disk 101 at the same time as when the loading is made.

After the loading operation, the head 102 is fed until the actuator 105 comes in contact with the stopper 103, and the head feeding pitch is determined for the writing of propagation-purpose pattern. This procedure (steps S) will be described with reference to FIGS. 4~6.

First, after step 23 in FIG. 2, the head is moved until the actuator is made in contact with the stopper on the innermost periphery, and then a certain DC current is caused to flow in the VCM so that the actuator can be pressed against the stopper as shown in FIG. 4 (step 41).

At this time, the value of the current flowing in the VCM is represented by 109-0. Also, a pattern of a constant frequency (All-1 pattern) is

written along one full circle on the disk 101 at the
radial position of the head corresponding to where the
actuator has been pressed against the stopper (S42).
Then, the current continuously caused to flow in the
5   VCM in order for the actuator to be pressed is
decreased in stages, and the head is started to move
toward the outer periphery. FIG. 5 shows the relation
between the VCM current and the radial position of the
head.

10   By gradually decreasing the VCM current,
which flows when the pattern has been written on the
disk at step 42, as shown at 109-0, 109-1, 109-2 in
turn, the head position is changed from 501-0 to 501-1,
501-2 toward the outer periphery.

15   FIG. 6 shows the relation between the radial
position of the head and the amplitude of the
reproduced signal. The amplitude of signal reproduced
at each stage to which the head is moved is converted
to a digital value by the demodulator 107d, and stored
20   in the memory 107g through the controller 107f (S43).

       As shown in FIG. 5, after the VCM current is
decreased up to a previously selected value 109-m in
order for the head to move to 501-m, it is increased up
to a previously selected value 109-n in order for the
25   head to move to position 501-n toward the inner
periphery (S44).

       The VCM current is again decreased from 109-n
to 109-(n+1) in stages in order for the head to move to

the position where the amplitude is the maximum, and
the amplitude at each stage is converted to a digital
value by the demodulator 107d, and stored in the memory
(S45).

5   Executing the procedure from step 401 to step
405 will form an off-track profile of reproduced
amplitude as represented by reference numeral 602 in
FIG. 6. The amount of R/W offset, 603 of the head is
calculated from the distance between the head position
10   501-a at which the All-1 pattern has been written and
the crest position (501-2, in this embodiment) of the
obtained off-track profile.

Additionally, at this stage the effective
track width is calculated. Typically, the magnetic
15   track width can be represented by the distance between
two points where the amplitudes in the off-track
profile are 50% of the maximum.

Thus, first, each of the values stored in the
memory, and a 50% value (602-h in FIG. 6) of the
20   maximum in the off-track profile are compared with each
other, i.e., the values stored in the memory that
correspond to a range of the profile on the outer
periphery side from the maximum amplitude point 501-2
are sequentially checked by comparing with the 50%
25   value of the maximum amplitude. The result is that a
point 501-e1 where the value stored in the memory
initially becomes smaller than the 50% value is decided
to be the edge position on the outer periphery side.

Similarly, the values stored in the memory that correspond to the other range of the profile on the inner periphery side are sequentially checked by comparing, so that the other edge point, 501-e2, on the

5 inner periphery side can be obtained. Thus, a track width 605 is calculated from the distance between both the obtained edges (S46).

The operation for calculating the head feeding pitch at step 25 in FIG. 2 will be next

10 described with reference to FIG. 6. At step 26, the head is offset a certain amount from the already recorded pattern, and a new track is recorded to form a pattern in that position.

This offset movement of the head is made by

15 positioning the head so that the amplitude of the reproduced signal from the already recorded track can reach the target value. The targeted amplitude value depends on the ratio of the head's track width to the track pitch in the associated magnetic disk device. In

20 this embodiment, the track pitch is selected to be 125% of the measured track width 605, and half the track pitch is decided to be a head feeding pitch 604.

In this case, the targeted amplitude value for the head to be fed to record is decided to be an

25 amplitude 602-t at a position 501-t that is separated by the R/W offset 603 and the pitch 604 away from the write position 501-a toward the outer periphery side in the off-track profile 602.

After the head 102 is fed up to the stopper
106 on the innermost periphery, the propagation-purpose
pattern is recorded by the procedure of steps 24, 25
and 26. When the head 102 arrives at around the
5 outermost periphery, the signal 304 written at the time
of loading is reproduced by the head 102.

FIG. 7 shows the reproduced waveforms of the
propagation-purpose pattern and the signal written at
the time of loading in this embodiment. A waveform
10 702a is a reproduced waveform in a place where the
signal recorded at the time of loading in step 27 is
not written. This reproduced waveform 702a is a
waveform reproduced when a propagation-purpose pattern
701c is used as a position signal. In this case, since
15 the signal recorded at the time of loading is not
written, no position signal is detected on the outer
periphery side of the propagation-purpose pattern 701c.

When the head reproduces the position signal
on the outermost periphery 701d in step 27, the pattern
20 signal written at the time of loading is reproduced
except the propagation-purpose pattern. At this time,
the reproduced waveform is a waveform 702b.

In this embodiment, the propagation pattern
is detected in its amplitude at time 701a, 701b, 701c
25 (701d, 701e, 701f), and the amplitude is converted to a
digital value by the demodulator 107d and supplied to
the controller 107f where the signals having larger
amplitudes than background noise are fed to a register

and counted.

Since the propagation-purpose pattern recorded from the inner periphery is written at a constant pitch on the disk, the number of detected signals having larger amplitudes than background noise is determined at certain points (three, as to the reproduced waveform 702a). However, on the outermost periphery, the signal written at the time of loading is also detected (four signals are detected as to the reproduced signal 702b). When more than four signals having large amplitudes than background noise are detected, the outermost periphery is detected.

When the propagation-purpose pattern is recorded up to the outermost periphery 110, the number of steps over which the head is fed can be known from the head feeding pitch 604 set in step 26. The head feeding pitch set in step 25 depends on the core width of the head, and thus the number of steps over which the head is fed varies due to the dispersion of the core width.

Thus, at the stage where the product-purpose servo signal is recorded, it becomes sometimes necessary that the feeding pitch be readjusted in order to provide a designed number of tracks. The feeding pitch of the product-purpose servo signal is readjusted according to the procedure (steps S) of FIG. 8 as follows.

The number of tracks, track pitch and head

core width designed are previously stored in the memory

107g (S81). The propagation-purpose pattern is

recorded in the radius direction, and the outermost

periphery is detected by recognizing the pattern

5 written at the time of loading (S82).

Until the outermost periphery is detected,

the number of steps over which the head is fed in order

to record the propagation-purpose pattern is counted by

the controller 107f, and stored in the memory 107g

10 (S83).

Then, the number of steps for the head to be

fed over is calculated by the controller 107f from the

designed track number, track pitch and head core width

stored in the memory 107g, and compared with the number

15 of steps over which the head has actually been fed

(S84). Specifically, the number of steps can be

calculated by multiplying the number of steps necessary

to record one track by the number of tracks.

If the number of steps differs in both the

20 designed and actual cases, the controller 107f can find

the head feeding pitch for recording the production-

purpose servo signal by multiplying the pitch at which

the head has actually been fed by the ratio of the

number of steps over which the head has actually been

25 fed to the designed one (S85). Subsequently, the head

is fed by a selected number of steps, and when the

production-purpose servo signal has been completely

recorded the servo-write operation is finished (S86).

A second method for detecting the outermost periphery will be described next. In this method, the surface of the disk 101 is divided into two regions that are alternately placed in the circumferential

5 direction as shown in FIG. 9. In other words, these regions are an area 901 in which no propagation-purpose pattern is written, and an area 902 in which it is written.

At the time of loading, the signal 110 is

10 written in the areas 901 in which no propagation-purpose pattern is written, in response to the timing signal generated from the spindle motor, and thus the areas 901 include the signal 110. The areas 901 in which no propagation-purpose pattern is written are

15 monitored in response to the timing signal from the spindle motor. Just when the reproduced waveform of signal 110 is detected, the point of this instant is decided to be the outermost periphery.

Thus, the servo signal can be recorded at

20 precisely a controlled track pitch by the head and actuator that the magnetic disk device itself has without recording a preliminary servo signal on a disk by using an external apparatus. Therefore, the clean room and external writing device can be omitted.

25 While the ramp road 103 is assumed to be on the outer periphery side in this embodiment, it may be provided on the inner periphery side provided that the positional relation between the inner and outer

peripheries is reversed in the above method, and in this case the same effect as in the above embodiment can be achieved.

It should be further understood by those skilled in the art that the foregoing description has been made on embodiments of the invention and that various changes and modifications may be made in the invention without departing from the spirit of the invention and scope of the appended claims.